



# Ampelok FASTENERS

*Fixing fibreglass sheeting to steel purlins*

## No pre-drilling of fibreglass sheeting required!

- Ensures correct hole size for thermal expansion and fastener is centred correctly.
- Fastener carries a Class 5 coating.
- For use with steel purlins up to 3.5mm thick.
- Can be supplied pre-painted to suit the roof colour.
- Ampelok fasteners come pre-assembled and packed in 10 litre plastic buckets in the follow quantities:
  - 14g x 75mm with the LR Washer - 300
  - 14g x 90mm with the LR Washer - 300
  - 14g x 75mm with the HR Washer - 250
  - 14g x 90mm with the HR Washer - 250
- Side Lap Stitching fasteners;
  - 12g x 40mm LR Washer - 400
  - 12g x 40mm HR Washer - 400
- Ampelok fasteners are supplied with universal Metal Profiled Washers and EPDM Seals to fit most of the common roofing profiles in NZ.
- The **LR Washer** fits the following profiles: Corrugated, 5 Rib, Trimdek, Veedek, Sixrib, Trimline, Plumbdek, MC700, MC750, MC770, Ribline, LT7, ST7, Silbery, DP955, Supersix.
- The **HR Washer** fits the following profiles: Steelspan, Topspan, Multispan, MC930, Maxispan, BB900, ST900, ST963, Multirib, Topspan, V Rib.

save up to  
**50%**  
installation time!  
*Pre-drills its own  
expansion  
hole.*



Ampelok screws and washers can be supplied painted safety RED to indicate where skylights are positioned on a roof to help eliminate damage from foot traffic.

Freephone: 0800 AMPELITE (0800 267 354)  
79 Captain Springs Rd, Onehunga, Auckland  
[www.ampelite.co.nz](http://www.ampelite.co.nz)

**AMPELITE**  
*makes light work!*